

ELECTRIC DRYER DEL-3899A
96 cm belt width, heat chamber 250cm

Machine

| | | | | |
|----|--|---|-----------------|--------------|
| 1 | Total length | 350 cm | | |
| 2 | Heat chamber length | 250 cm | | |
| 3 | Belt width | 96 cm | | |
| 4 | Inlet / outlet length | 50 cm or customized | | |
| 5 | High | 115 cm | | |
| 6 | Electrical requirements | 400V, 3PH, 16 kW, 32A CEE-plug | | |
| 7 | Belt rotation direction | Both side(left & right) | | |
| 8 | Belt drive | frequency converter, sleeplessly adjustable | | |
| 9 | Belt type | fiberglass Teflon coated, 4x4 mm mesh-size | | |
| 10 | Exhaust connection | 125 mm | | |
| 11 | Heating elements | 3.3 um IR wave length | | |
| 12 | Temperature control | PID | | |
| 13 | Cool skin technology | 150 mm insulation 4 walls | | |
| 14 | If equipped with Hot air circulation cures wide range of inks with all substrates (also paper and plastic) | Plastisol Inks | Water base Inks | Solvent Inks |
| 15 | Guarantee | 2 years limited warranty | | |
| 16 | Production capacity (curing element size 40 x 50 cm, curing conditions 1 min in 160°C) | 600 pcs/hr | | |

MACHINE EQUIPMENT IN OPTION

| | | | | | |
|----|--|--------|---|--|--|
| 17 | Wheels option per 1 oven | YES | 1 | | |
| 18 | Hot air circulation* per 1 oven (1300 m ³ /h) | YES | 1 | | |
| 19 | Cooling System | OPTION | 1 | | |